

# PELLET AIR DUCTABLE FANCY 12 PJ



## FANCY 12 PJ

Energy efficiency class	A+	
Conformity	EN 14785: 10-2006	
Dimensions	L 58 x P 60 x H 115 cm	
Packing dimension	0,60 m <sup>3</sup>	
Net weight	kg 129	
Heat Output	kW 12,0	
Nominal Heat Output	kW 10,5	
Minimum Heat Output	kW 4,8	
Efficiency	min 93,2 %	max 87,2 %
CO emissions (13% O2)	min 237 mg/Nm <sup>3</sup>	max 67 mg/Nm <sup>3</sup>
CO emissions (13% O2)	min 0,019 Vol.-%	max 0,005 Vol.-%
OGC emissions (13% O2)	min 3 mg/Nm <sup>3</sup>	max 2 mg/Nm <sup>3</sup>
NOx emissions (13% O2)	min 137 mg/Nm <sup>3</sup>	max 134 mg/Nm <sup>3</sup>
Dust content at average (13% O2)	14,9 mg/Nm <sup>3</sup>	
Flue draught	min 10 Pa	max 12 Pa
Exhaust pipe diameter	Ø 80 mm	
Intake duct diameter	Ø 50 mm	
Ducting pipe diameter	Ø 60 mm	
Hopper capacity	kg 16	
Pellet Consumption	min 1,06 kg / h	max 2,48 kg / h
AC voltages	V/HZ 230 / 50	
Nominal electricity absorption	min 106 W	max 120 W
Ignition electricity absorption	320 W	
Heating capacity m <sup>3</sup>	127 / 277 m <sup>3</sup>	
Noise level dBA	dB 42 / 49	
Fuel	PELLET EN PLUS A1	

## PLUS

- Airtight room
- 1-2 ducting engines
- Cast iron brazier
- Poujoulat duct 80/130
- Uniform heat
- Exhaust pipe on top
- Temperature Modulation system
- Silent function (u.c. lowered power)
- Daily/Weekly planning
- 5-level Power
- 7-language display
- Cool-touch handle
- Glass-ceramic

## FINITIONS



Metal  
White



Metal  
Aluminium



Metal  
Black



Metal  
Taupe

## OPTIONEEL

- Wi-Fi
- Remote control
- Ductable kit
- Ash pan