


PELLET AIR DUCTABLE KING 12



Le label
du chauffage
au bois

Appareil de classe



KING 12

Energy efficiency class	A+	
Conformity	EN 14785: 10-2006	
Dimensions	L 54 x P 53 x H 104 cm	
Packing dimension	0,55 m ³	
Net weight	kg 102	
Heat Output	kW 12,0	
Nominal Heat Output	kW 10,5	
Minimum Heat Output	kW 4,8	
Efficiency	min 93,2 %	max 87,2 %
CO emissions (13% O ₂)	min 237 mg/Nm ³	max 67 mg/Nm ³
CO emissions (13% O ₂)	min 0,019 Vol.-%	max 0,005 Vol.-%
OGC emissions (13% O ₂)	min 3 mg/Nm ³	max 2 mg/Nm ³
NOx emissions (13% O ₂)	min 137 mg/Nm ³	max 134 mg/Nm ³
Dust content at average (13% O ₂)	14,9 mg/Nm ³	
Flue draught	min 10 Pa	max 12 Pa
Exhaust pipe diameter	Ø 80 mm	
Intake duct diameter	Ø 50 mm	
Ducting pipe diameter	Ø 60 mm	
Hopper capacity	kg 26	
Pellet Consumption	min 1,05 kg / h	max 2,48 kg / h
AC voltages	V/HZ 230 / 50	
Nominal electricity absorption	min 106 W	max 120 W
Ignition electricity absorption	320 W	
Heating capacity m ³	127 / 277 m ³	
Noise level dBA	dB 42 / 49	
Fuel	PELLET EN PLUS A1	

PLUS

- Airtight room
- 1-2 ducting engines
- Cast iron brazier
- Uniform heat
- Rear side exhaust pipe and on top
- Temperature Modulation system
- Silent function (u.c. lowered power)
- Daily/Weekly planning
- 5-level Power
- 7-language display
- Cool-touch handle
- Glass-ceramic

FINISHING



Metal
Red



Metal
White



Metal
Anthracite

OPTIONAL

- Wi-fi
- Remote control
- Ductable kit
- Ash pan