

PELLET AIR  
KUBE 9.0



Le label  
du chauffage  
au bois



### KUBE 9.0

Energy efficiency class	A+	
Conformity	EN 14785: 10-2006	
Dimensions	L 46 x P 49 x H 93 cm	
Packing dimension	0,53 m <sup>3</sup>	
Net weight	kg 72	
Heat Output	kW 9,28	
Nominal Heat Output	kW 8,5	
Minimum Heat Output	kW 2,6	
Efficiency	min 93,5 %	max 91,5 %
CO emissions (13% O <sub>2</sub> )	min 171 mg/Nm <sup>3</sup>	max 92 mg/Nm <sup>3</sup>
CO emissions (13% O <sub>2</sub> )	min 0,014 Vol.-%	max 0,007 Vol.-%
OGC emissions (13% O <sub>2</sub> )	min 4 mg/Nm <sup>3</sup>	max 2 mg/Nm <sup>3</sup>
NOx emissions (13% O <sub>2</sub> )	min 116 mg/Nm <sup>3</sup>	max 117 mg/Nm <sup>3</sup>
Dust content at average (13% O <sub>2</sub> )	15 mg/Nm <sup>3</sup>	
Flue draught	min 10 Pa	max 12 Pa
Exhaust pipe diameter	Ø 80 mm	
Intake duct diameter	Ø 40 mm	
Hopper capacity	kg 22	
Pellet Consumption	min 0,56 kg / h	max 1,91 kg / h
AC voltages	V/HZ 230 / 50	
Nominal electricity absorption	min 37 W	max 77 W
Ignition electricity absorption	350 W	
Heating capacity m <sup>3</sup>	68 / 224 m <sup>3</sup>	
Noise level dBA	dB 37 / 46	
Fuel	PELLET EN PLUS A1	

### PLUS

- Airtight room
- Cast iron brazier
- Rear side exhaust pipe
- Temperature Modulation system
- Silent function (u.c. lowered power)
- Daily/Weekly planning
- 5-level Power
- 7-language display
- Cool-touch handle
- Glass-ceramic

### FINISHING



Metal  
Red



Metal  
White



Metal  
Anthracite

### OPTIONAL

- Wi-fi
- Remote control
- Ash pan